

PIVOT ASPHALT ROLLER

Dynapac CG2300



Atlas Copco



Instead of central articulation, machines in the Dynapac CG roller range traditionally have steering on the drums. Atlas Copco Road Construction Equipment is now introducing the new Dynapac CG2300, as a supplement to its articulated CC machines. The Dynapac CG2300 is 3.99 m long, 2.99 m high and has an inner turning radius of only 2.65 m, and an off-set as big as 1.2 m, making it easy to transport and manoeuvre in confined spaces.

COMPACT COMPACTION

DESIGNED WITH THE OPERATOR IN MIND

The cab on the Dynapac CG2300 was designed with the operator in mind. The interior offers the highest level of comfort and the drum edge visibility is excellent thanks to the extended sideways sliding seat and steering assembly. An Automatic Climate Control system is available as an option. Good ergonomics, plus smooth and precise steering are features provided by the advanced electronic mini steering wheel and four-piston steering system.

Optimized ergonomics is one way to achieve high quality compaction, ensuring that operators have continuous visibility of the operation and comfortable access to the controls. The CG2300 will feature 1 x 1 meter view and full visibility over all working functions including the drum surface/ sprinkler nozzles.

The clear control panel gives operators the information they need. All the gauges are displayed – water, fuel, voltage and number of hours – and the operator can change between menus at the touch of a button. Further information can be provided through the optional Dyn@Lyzer software, which gives the full documentation of temperature, compaction Evib value and number of passes on each section of the asphalt

QUIET RUNNING WITH GOOD FUEL ECONOMY

The Dynapac CG2300 is equipped with ECO Mode as standard. This reduces fuel consumption by more than 15% and makes the already quiet CG roller even more silent. Noise is also kept down through the use of a hydraulic driven temperature-guided cooling fan, which only operates when necessary.

Use of a double pump vibration system eliminates the need for a vibration valve, making the system more efficient, aiding servicing and reducing fuel consumption. Both pumps – one for the front drum and one for the rear – can simply be shut off.

The CG2300 has got automatically cut to idling speed after 10 seconds at full rpm in neutral, in recognition of the fact that operators often neglect to make the reduction themselves.

In addition, the engine is Stage IIIB/T4f ready and has very low emissions. Advanced options are also available, such as an edge presser/cutter (left and right) and a chip spreader.

A sprinkler system with double sprinkler bars and pumps, and a capacity of more than 700 liters of water, ensures uninterrupted operation.





VISIBILITY

1 x 1 meter forwards and backwards. Good drum surface and sprinkler nozzle visibility. Full visibility of the drum edges

CAB

Low noise level ROPS/FOPS cab with optional automatic climate control system

OFF-SET DRUM

A maximum off-set of 1200 mm as standard



LOW EMISSIONS

EcoMode as standard keeps rpm, fuel consumption and noise on a very low level. More than 15% fuel consumption reduction. Stage IIIB and T4 final ready engine.

SERVICEABILITY

Easy to reach service points and long intervals. Service "Pop ups" on the display



Total length 3.99 m



COMPACT COMPACTION



Height: 2,99 m

EASY NIGHTWORK

LED main working lights, drum edge lights and drum surface lights as standard

ERGONOMICS

Fully rotating and slide-able operators module with mini steering wheel, instrument panel and F&R handle that follows the module



COMPACT AND MANOEUVRABLE

Only 3.99 m long, 2.99 m high, an inner turning radius of 2.65 m and a large off-set of 1.2 m makes the CG2300 very easy to manoeuvre in confined spaces.

VISIBILITY

Visibility of 1x1 meters forwards and backwards makes the Dynapac CG2300 safe for people working around the machine and facilitates the driving for the roller operator.

Drum surfaces are visible thanks to the open frame and drum surface lights. This helps to maintain full control of the watering of the drums to avoid asphalt picking.

The large openable windows and the wide sliding function gives the operator full visibility of the drum edges.

CAB AND ERGONOMICS

The fully rotating and slide-able operator module makes it possible for the operator to be placed for best visibility and ergonomics.

For optimum control the instrument panel, F&R handle and electronic mini steering wheel always follows the module.

Big openable side windows together with full slideability of the seat and steering module makes it easy for the operator to find a comfortable position with good visibility.

The noise level is very low in the ROPS/FOPS cab and Automatic Climate Control is available as an option.



SERVICEABILITY

Spring loaded scrapers keep adjustment time low and are easy to release and apply.

The lockable compartment for the rotating beacons keep them well protected against vandalism and theft.

All daily servicepoints are easy to reach also at night thanks to engine compartment light.



OPTIONS FOR ALL APPLICATIONS

An optional chipspreader is available for surface treatment on hot asphalt mix.

An optional edge presser for pressing of joint surface and outer asphalt edge is also available. Just changing the tool to a cutting disc and start cutting.



EASY NIGHTWORK

LED main working lights give a very white light that makes it possible to see if the mat is uneven and eventual marks also in the night.

Drum edge lights on all four drum forks gives visibility on all the drum edges and edge pressers/ cutters



Drum surface lights helps the roller operator to keep full control of the watering of the drums to avoid asphalt picking

Engine room lights facilitates service done in the night



Lights on the steps makes it safer and easier to enter and leave the machine

COMPACTION CONTROL WITH DYN@LYZER

DYNAPAC'S EXPERIENCE in Continuous Compaction Control (CCC) or Intelligent Compaction (IC) dates back to the late 70s. Since then we have been able to offer our customers the opportunity to control the compaction work in real time and to document the completed work for improved quality control.

DYN@LYZER for Asphalt

Compaction Documentation

Records and maps in real time:

- Compaction Meter values
- Progress of Compaction Meter values, relative
- Temperature Meter values
- Number of passes
- Supports the roller operator to optimize compaction effort

Analysis of the compaction

- Compaction Meter values (stiffness)
- Progress of Compaction Meter values (progress of stiffness)
- Temperature
- Number of passes
- Statistics and distribution
- Export PDF report and data text file

Facts about the DYN@LYZER

- Multiple machines can be factory prepared. This ensures a cost effective way to prepare a fleet of machines with the DYN@LYZER as they can share DYN@LYZER computer and GNSS equipment for use as required.
- User-friendly, modern user interface
- 11.6" full color touch screen
- Electronic keyboard for entry of data
- Mobile memory for permanent storage
- Several languages to choose from
- Runs on the roller's 24V battery or internal battery
- Tablet weight: 1.4 kg
- 220V adapter for office use
- Rugged tablet, resistant to dust, moisture and vibrations
- In Multi version, office software is included as well as machine-to-machine communication

TECHNICAL DATA

DYNAPAC CG2300

Drum width, mm 1500

MASSSES

Operating mass , kg (incl. ROPS) 7,900
Module mass, kg (front/rear) 3,950/3,950

TRACTION

Speed range 0-12
Vertical oscillation $\pm 6^\circ$
Theor. gradeability 41

COMPACTION

Centrifugal force , kN (high/low amplitude) 80/60
Nominal amplitude, mm (high/low) 0.6/ 0.3
Static linear load kg/cm (front/rear) 26.3/26.3
Vibration frequency, Hz (high/low amplitude) 45/55
Water tank, l 740

ENGINE

Manufacturer/Model Deutz TD3.6 L4 T4F
Type Water cooled turbo Diesel
Rated power, SAE J1995 55 kW (74 hp)@ 2,200 rpm
Fuel tank capacity, l 115



STANDARD FEATURES FOR CAB

Integrated ROPS/FOPS
Operator's station, sliding and rotating
Seat belt 3" with buzzer
Heating system
Frequency meter/ impactometer
Multi speed fan system with filter
Floor mat
Panel covers, interior
Inner roof noise absorbing
Internal rear view mirror
Interior light
Charger socket: One 24 and one 12 Volts
Steering wheel, mini in armrest
Storage: Rear cover and side panel
Cup and can holder
Tinted safety glass
Openable sidewindows
Wipers and washers front and rear
Rear view mirrors, traffic view
Water level display
Speedometer display
Hour meter display
Engine temperature display
Fuel level display
Hydraulic fluid temperature display
I/O-list in machine display
Tachometer display
Voltage meter display
Warning light, air cleaner
Warning light, clogged hydraulic fluid filter
Warning light, engine oil pressure
Warning light, engine oil temperature
Warning light, hydraulic fluid temperature
Warning light, low charge
Warning light, low fuel level
Drive control, electronic (EDC)
Speed limiter

OPTIONAL FEATURES FOR CAB

Comfort cab incl:
ACC (Automatic Climate Control)
Radio with MP3
Operators seat, luxury

OTHER STANDARD FEATURES

Amplitudes, dual. French V1 class
Automatic Water Control (AWC)
Automatic Vibration Control (AVC)
Back up alarm
Bio fuel ready B20
Brake release
CE-mark
ECO-mode
Flow divider
Lifting points
Lights, working LED
Offset drums
Rear view mirrors, process view
Rotating beacon
Spring loaded scrapers
Split drums
Sprinkler, panic button
Spinkler system pressurized with 3-stage filtering and back up system with dual sprinkler bars
Sprinkler timer
StageIV/Tier4 diesel engine
Tie down points
Tool box
Vibration quick stop
Vibration shut off, front or rear drum

OTHERS OPTIONAL FEATURES

Asphalt temperature meter
Biodegradeable hydraulic fluid
Chip spreader
Chip spreader, preparation
Dynapac Compaction Analyzer
Edge press, right side
Edge press, left side
Fire extinguisher
First aid kit
Joint cutter disc, 150 mm (5.9 inch) cutting depth
Joint cutter disc, 80 mm (3.1 inch) cutting depth
Lights, direction, side mounted
Lights, driving for chip spreader
Lights, driving, right hand traffic
Lights, licence plate
Rotating beacon, dual LED
Service Kit 50/500/1000 hours
Slow Moving Vehicle sign
Special colour, one or two colours
Steering, emergency
Tachograph
Tool set
Water tank cover, lockable

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.
The above information is a general description only, all informations are supplied without liability.

COMMITTED TO SUSTAINABLE PRODUCTIVITY

We stand by our responsibilities towards our customers, towards the environment and the people around us. We make performance stand the test of time.

This is what we call - Sustainable Productivity.

Dynapac Compaction Equipment AB

Industrivägen 2, 371 31 Karlskrona, Sweden
Phone: +46 455 30 60 00 - Fax: +46 455 30 60 30 www.atlascopco.com

Atlas Copco